



PRODUCTS™

1-87-STOCKTON

FAX: (702) 651-0948

office@stocktonproducts.com

FaceBook.com/stocktonproducts


www.StocktonProducts.com

BNII: Bullnose II


Used when the strongest rounded corners are desired. Comes with a standard 7/16" radius (ping pong ball size). Standard 2 1/2" legs. DoubleWire has an additional wire on the outside edges to provide additional nail points. Extra nose wires provide increased structural rigidity.

Galvanized: 10BNII716 (7/16")

Stainless Steel: 10SSBNII716 (7/16")



Length	Feet Per Carton
10 Ft.	400 Ft./Ctn.



Materials:

- Galvanized (17.5 Gauge Wire)
G-60 Coating
- Stainless Steel (17.5 Gauge Wire)
316L Stainless 18% Chromium

Note: Standard length is 10 feet.
Additional lengths available upon request.

ASTM Codes:

- A580/A580M (Stainless Steel)
- A641/A641M (Galvanized Wire)
- A653/A653M (Galvanized Coating)
- A924 (Galvanized Steel)
- C1047 (Drywall)
- C1063 (Accessories)
- C1063 (Accessories)
- C841 (Interior Furring & Lathing)

©2016 Stockton Products. All rights reserved worldwide. CornerAid®, WeepAid®, Pozalite®, ArchAid®, StockAid®, EmberStop®, BugStop®, SolidGround®, Tru-Corner® and Superior Moisture Protection™ are all trademarks of Stockton Products™.

