



PRODUCTS™

**1-87-STOCKTON**

FAX: (702) 651-0948

office@stocktonproducts.com



FaceBook.com/stocktonproducts

www.StocktonProducts.com


## J-B: J Bead

- Superior Moisture Protection™
- Available With 1/8", 1/2" Weep Holes or No Weep Holes
- Available in Copper, Galvanized Steel, Zinc, Stainless Steel or Aluminum

Standard plaster stop/casing bead for terminating stucco. Has a return key for finishing. Matching factory miter-cut, solid-soldered inside and outside corners are available, giving you moisture management confidence throughout the entire installation.



### KEY



Length	X Size	Y Size
10'	3/8"	3 1/2"
	1/2"	5"
	3/4"	
	7/8"	
	1 1/8"	
	1 1/4"	
	1 3/8"	
	1 1/2"	
	2"	

### Materials:

- Copper (24ga. - 0.0216" - 16oz)
- Galvanized Steel (26ga. - 0.0217" - G90)
- Zinc (24ga. - 0.0200" - #190)
- Stainless Steel (26ga. - 0.0187" - SAE 304)
  - #2B (Dull Finish)
  - #4 (Brushed Finish)
  - #8 (Mirror Finish)
- Aluminum (22ga. - 0.0253" - 5052 H32)

**Note:** Standard length is 10 feet.  
Additional lengths available upon request.

### ASTM Codes:

- A580M (Stainless Steel)
- A653/A653M (Galvanized Coating)
- A924 (Galvanized Coating)
- B152/B152M (Copper)
- B209 (Aluminum Sheet)
- B69 (Zinc)
- C1047 (Drywall)
- C1063 (Accessories)
- C841 (Interior Furring and Lathing)

